

Keg coolers



The keg coolers are supplied "flat pack" and can be assembled in minutes in some of the most inaccessible sites.

The FK/MUP not only serves to refrigerate the kegs in the keg cooler, but also cools the water in the python system running to the beer tap. The reinforced bottom is made from Stainless Steel (AISI 304, 18/10) and has on 3 sides a moulded edge. The keg coolers are also very suitable for cooling beverages in crates.

Keg coolers

Finish exterior: anthracite skin plate

Finish interior: silver coloured skin plate (bottom: stainless steel (AISI 304, 18/10))

Without machine unit...



Keg cooler box**

- Capacity: 2 x 50 L or 4 x 30 L
- Dimensions exterior W x D x H without feet: 1060 x 713 x 1060 mm and with feet: 1060 x 713 x 1080/1100 mm
- Dimensions interior W x D x H: 980 x 620 x 980 mm

FK/2



Keg cooler box**

- Capacity: 4 x 50 L or 8 x 30 L
- Dimensions exterior W x D x H without feet: 1060 x 980 x 1060 mm and with feet: 1060 x 980 x 1080/1100 mm
- Dimensions interior W x D x H: 980 x 885 x 980 mm

FK/4



Keg cooler box**

- Capacity: 6 x 50 L or 12 x 30 L
- Dimensions exterior W x D x H without feet: 1465 x 980 x 1060 mm and with feet: 1465 x 980 x 1080/1100 mm
- Dimensions interior W x D x H: 1385 x 885 x 980 mm

FK/6



Keg cooler box**

- Capacity: 8 x 50 L or 16 x 30 L
- Dimensions exterior W x D x H without feet: 1870 x 980 x 1060 mm and with feet: 1870 x 980 x 1080/1100 mm
- Dimensions interior W x D x H: 1790 x 885 x 980 mm

FK/8



Keg cooler box**

- Capacity: 10 x 50 L or 20 x 30 L
- Dimensions exterior W x D x H without feet: 2200 x 980 x 1060 mm and with feet: 2200 x 980 x 1080/1100 mm
- Dimensions interior W x D x H: 2120 x 885 x 980 mm

FK/10

** machine unit is required

Machine units

Climate class N: functions optimally in surrounding temperatures of up to 32°C / 90°F.
Finish exterior: anthracite skin plate - Voltage range: 220-240 V / 50Hz / 1~

Plug ready



For use with FK/2, 4, 6, 8 or 10 (to be fitted in top)

- Cooling capacity: 463 W* (8,8 cc)
- Power consumption: 385 W*
- Temperature range: +2°C / +12°C
- Dimensions W x D x H: 612 x 523 x 310 mm

FK/MU



Machine unit with circulation pump for use with FK/2, 4, 6, 8 or 10 (to be fitted in top)

- Cooling to kegs and python line
- Cooling capacity: 587 W* (12,05 cc)
- Power consumption: 510 W*
- Temperature range: -3 / +8°C (python line), +2°C / +12°C (keg cooler)
- Dimensions W x D x H: 870 x 523 x 370 mm

FK/MUP

*conditions : Te = -5°C, Tc = 45°C, ambient = 25°C