

Beverage Dispensing System Chilled juice dispenser with 2- flavor dispensers

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____


560300 (LCD-2C-22)

Chilled Juice Dispenser with 2-flavor dispensers (5 l capacity container/BiB each), refrigerated chamber, stainless steel Cabinet, digital control and LCD display

Short Form Specification

Item No. _____

The 5 liters containers liquid concentrate dispenser is ideal to dispense cold liquid juice, coffee, etc... It features low level indicator, LED light for the cup location, drip tray with overflow indicator and LED illuminated graphics to increase visibility. LCD digital control for product ration and temperature setting; LED illuminated dispense button and product label. Stainless steel panels and splash zone and no visible screw on the external body guarantee hygiene and easy cleaning.

Main Features

- The liquid concentrate dispenser is ideal to dispense cold liquid juice, coffee, etc...
- The Automatic Portion Dispense allows to adjust and control the product ratio and easily replace the cup for self-service application.
- The low level indicator inform when it is required to fill more product.
- LED light for the cup location.
- Drip tray with overflow indicator.
- LED illuminated graphics bring high visibility to front.
- LCD digital control for product ration and temperature setting.
- LED illuminated dispense button and product label.
- Stainless steel panels and splash zone and no visible screw on the external body guarantee hygiene and easy cleaning.
- Dedicated cleaning cycle for pump sanitization.
- 19 cm (7.5") cup clearance accommodates most juice containers.
- Product ratio between 1:3 to 1:9. Higher ratio can be customized.
- Automatic portion dispenser or manual dispense.
- Direct connect to water supply.
- Pre-post function for best product mix.
- Burst capacity: at rate of one 355ml (12 oz) drink/min, 70 drinks before exceeding 5°C (41° F) - 24°C (75°F) ambient and 24°C (75°F) incoming water temperature.

Construction

- 2 heads to dispense 2 flavours.
- Digital control.
- LCD display
- 5 liters containers.
- Fully sealed internal compartment.
- Include condenser filter.

APPROVAL: _____



Electric

Supply voltage:

560300 (LCD-2C-22) 220-240 V/1N ph/50/60 Hz

Key Information:

External dimensions, Width: 280 mm

External dimensions, Height: 845 mm

External dimensions, Depth: 680 mm

Net weight: 55 kg

Refrigeration Data

Refrigerant type: ;R134a

